




# TOPWOOD

Top Quality Top Value Top Service

## TOPWOOD GUARANTEED



## 2025 BROCHURE<sup>v17</sup>

TOPWOOD GARDEN BUILDINGS LTD



# TABLE OF CONTENTS

## TABLE OF CONTENTS

<i>Shed Type / Section</i>	<i>Page</i>
 Workshops	2
 Pent & Apex Sheds	3 - 6
 Corner Shed	7
 Summer House Conversions	8 - 9
 Garden Leisure	10 - 12
 Potting Sheds	13 - 14
 Summer House / Chalet Range	15 - 19
 Childrens Playhouses	20 - 24
 Mini Sheds	25 - 27
 Roofing Options	28
 Sectional Buildings	29 - 30
 Single Glazed Windows & Doors	31
 Double Glazed Windows & Doors	32
 Insulation & Lining Options	33
 Optional Extras	34

# WORKSHOPS

WOODCOCK = APEX ROOF / WOODPECKER = PENT ROOF



WOODPECKER & WOODCOCK



10x8ft, Rustic Roof, 1 Extra Fixed Window  
Pressure Treated & Solvent Treated



Standard Specification Includes:

#### QUALITY T&G SHIPLAP CLADDING

100% timber construction (Untreated)  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
47x75 (45x70mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
4 3x2ft windows (3 fixed / 1 opening)  
1 Pair of 4' wide double doors  
24 kg felt, fittings, glass, padbolt  
Instructions for self assembly

**Apex Design:** Height to eaves 6'9" int / Height to ridge 8' int

**Pent Design:** Low height: 6'9" int / high side 7'5" int



Optional Extras Available - See Page 34 For Full List

#### Popular Sizes: Width X Depth

| 8' x 8' | 9' x 8' | 9' x 8' | 10' x 8' | 11' x 8' | 12' x 8' | 13' x 8' | 14' x 8' | 15' x 8' | 16' x 8' |  
| 16' x 8' | 17' x 8' | 18' x 8' | 19' x 8' | 20' x 8' | 9' x 9' | 10' x 9' | 12' x 9' | 14' x 9' |  
10' x 10' | 12' x 10' | 14' x 10' | 16' x 10' | 18' x 10' | 20' x 10' | 22' x 10' | 24' x 10' |



#### Selection of Client Woodpecker & Woodcock Customisations



18x10ft, Woodcock, Security Doors With Hook & Band Hinges, Rustic Roof



8x8ft, Woodcock, Rustic Roof  
Pressure Treated & Solvent Treated



8x8ft, Woodcock, Rustic Roof  
Pressure Treated & Solvent Treated



12x8ft, Woodpecker, 4' Double Security



16x10ft, Woodpecker, Security Door,



12x8ft, Woodpecker, 4' Double Security  
Doors, Pressure Treated & Solvent Treated

We can build to any size and design

# PENT & APEX SHEDS



Model: Robin



Standard 8x6ft, Pressure Treated & Solvent Treated



Standard Specification Includes:

## FEATHEREDGE CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
25x150 (15>5mm) featheredge cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings, glass, single door, padbolt  
Instructions for self-assembly  
Height to eaves 6' int (Approx.)  
Height to ridge 7'2" > 7'10" int (Approx.)

( Number of Windows will vary according to building size )



Optional Extras Available - See Page 34 For Full List

## Popular Sizes: Width X Depth:

| 4' x 4' | 5' x 4' | 6' x 4' | 7' x 5' | 8' x 6' | 10' x 6' | 10' x 8' | 12' x 8' |



## Selection of Client Customisations of the Robin Model



10x10ft, Security Windows  
Pressure Treated & Solvent Treated



10x6ft  
Pressure Treated & Solvent Treated



6x8ft, Nuthatch Windows + Doors  
Rustic Roof.  
Pressure Treated & Solvent Treated



8x6ft  
Pressure Treated & Solvent Treated



8x6ft, No Windows  
Pressure Treated & Solvent Treated



6x8ft, 3ft Door  
Pressure Treated & Solvent Treated

We can build to any size and design

# PENT / APEX SHEDS



Model: Wren



6x4ft, Pressure Treated & Solvent Treated



Standard Specification Includes:

## FEATHEREDGE CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
25 x150 (15>5mm) featheredge cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings, glass, single door, padbolt  
Instructions for self-assembly  
Low Height 6'2" int (Approx.)  
High Height 7'2" int (Approx.)

(Number of windows will vary according to building size )



Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth:

| 4' x 4' | 5' x 4' | 6' x 4' | 7' x 5' | 8' x 6' | 10' x 6' | 10' x 8' | 12' x 8' |

### Selection of Client Customisations of the Wren Model



7x5ft ( D )



8x6ft, Low Front




6x4ft ( D )



7x5ft ( E )



With Optional Shelf



6x4ft ( C )

### Pent Range Styles



A



B



C



D



E



F

We can build to any size and design

# PENT / APEX SHEDS



Model: Jay



8x6ft Solvent Treated



Standard Specification Includes:

#### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings, glass, single door, lock & key  
Instructions for self-assembly  
Height to eaves 6'0" int (Approx.)  
Height to ridge 7'2" > 7'10" int (Approx.)

( Number of windows will vary according to building size )



Optional Extras Available - See Page 34 For Full List

#### Popular Sizes: Width X Depth:

| 6' x 4' | 7' x 5' | 8' x 6' | 10' x 6' | 10' x 8' | 10' x 10' | 12' x 6' | 12' x 8' | 12' x 10' | 14' x 8' |



#### Selection of Client Customisations of the Jay Model



7x7ft, 5' Double Doors, Rustic Roof, Pressure Treated & Solvent Treated



8x6ft Stable Door, 3 Opening Widows Pressure Treated & Solvent Treated



10x6ft, Pressure Treated



8x8ft, Stable Door, 2 Opening Windows Pressure Treated & Solvent Treated



6x8ft, 2ft Roof Overhang, Rustic Roof Pressure Treated & Solvent Treated




8x10ft, Housemartin Windows, 2ft Roof Overhang, Solvent Rustic Roof Pressure Treated Building

We can build to any size and design

# PENT / APEX SHEDS



Model: Owl



6x4ft Owl, Bearers, Pressure Treated & Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings, glass, single door, lock & key  
Instructions for self-assembly  
Height to eaves 6'0" int (Approx.)  
Height to ridge 7'2" > 7'10" int (Approx.)



Optional Extras Available - See Page 34 For Full List

## Popular Sizes: Width X Depth

| 6' x 4' | 7' x 5' | 8' x 6' | 10' x 6' | 10' x 8' | 10' x 10' | 12' x 6' | 12' x 8' | 12' x 10' | 14' x 8' |



## Selection of Client Customisations of the Owl Model



12x5ft ( D )  
5' Double Doors  
Pressure Treated & Solvent Treated



12x8ft ( D )  
Pressure Treated & Solvent Treated



12x10ft ( C )  
Solvent Treated



12x6ft ( D )  
Pressure Treated & Solvent Treated



12x6t ( C ) Double Doors  
Pressure Treated & Solvent Treated



10x8ft ( C ) Security Door, Onduline Roof  
Pressure Treated, 2 - 3x2ft Opening Windows

## Pent Range Styles



A



B



C



D



E



F

We can build to any size and design

# CORNER SHED



## Model: Crow



8x8ft Pressure Treated

### Popular Sizes: Width X Depth:

| 7' x 7' | 8' x 8' | 9' x 9' |



## Model: Dove



8x8ft, Pressure Treated & Solvent Treated

### Popular Sizes: Width X Depth:

| 7' x 7' | 8' x 8' | 9' x 9' |



Optional Extras Available - See Page 34 For Full List



Standard Specification Includes:


### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings, glass, 4ft double doors, padbolt  
Instructions for self-assembly  
Height front 6'10" int (Approx.)  
Height back 6'0" int (Approx.)

➡ Optional Extras Available - See Page 34 For Full List

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
Includes full glass double doors  
2 top opening windows  
24 kg felt, fittings, toughened glass,  
Antique door furniture  
Instructions for self-assembly  
Height front 6'10" int - Height back 6'0" int (Approx.)



We can build to any size and design

# SUMMER HOUSE CONVERSIONS



Model: Sparrow



6x8ft, Pressure Treated & Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
18" Roof overhang as standard  
24kg felt, fittings, glass, single door, lock & key  
4 fixed windows, instructions for self-assembly  
Height to eaves 5'6 int (Approx.)  
Height to ridge 7'6" > 7'10 int (Approx.)



Optional Extras Available - See Page 34 For Full List

## Popular Sizes: Width X Depth:

| 4' x 8' | 6' x 8' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 6' x 10' | 8' x 10' | 10' x 10' | 12' x 10' |



6x8ft, Pressure Treated



5x8ft, Pressure Treated



5x7ft, Solvent Treated



6x10ft, Rustic Roof, Pressure Treated



6x8ft, Solvent Rustic Roof, Pressure Treated Building

We can build to any size and design

# SUMMER HOUSE CONVERSIONS



Model: Osprey I



6x8ft ( I ) Pressure Treated & Solvent Treated



Model: Osprey II



6x8ft ( II ) Pressure Treated & Solvent Treated  
( Optional 2ft Verandah )

## Popular Sizes: Width X Depth:

| 4' x 8' | 6' x 8' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 16' x 8' | 6' x 10' | 8' x 10' | 10' x 10' | 12' x 10' | 14' x 10' | 16' x 10' |

## Customisations of the Osprey I & II Models



8x8ft ( I ) 3ft Verandah , Rustic Roof,  
Opening Windows.  
Pressure Treated & Solvent Treated



8x10ft ( II ) Double Doors, Loglap Cladding,  
3 Opening Windows, Rustic Roof,  
Pressure Treated & Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
22" Roof overhang as standard  
3 fixed leaded windows  
24kg felt, flower boxes  
Fittings, glass, single door, lock & key  
Instructions for self assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 7'10" int (Approx.)  
Osprey I : Stable Door  
Osprey II : Leaded Glazed Door



Optional Extras Available - See Page 34 For Full List

We can build to any size and design

## Model: Skylark



10x6ft, Pressure Treated & Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 16x125 (12x119mm) T&G shiplap cladding  
 38x50 (34x45mm) prepared framework  
 Diagonal bracing for extra building strength  
 16x125 (12x119mm) T&G floor and roof  
 24kg felt, fittings, toughened glass, single door,  
 lock & key  
 4 fixed windows, 36" Roof overhang as standard  
 Instructions for self-assembly  
 Height to eaves 6'6" int (Approx.)  
 Height to ridge 7'1" int (Approx.)

Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth:

| 6' x 6' | 8' x 6' | 10' x 6' | 12' x 6' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 10' x 10' | 12' x 10' | 14' x 10' |

## Model: Animal Enclosure



8x6ft, Pressure Treated & Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 16x125 (12x119mm) T&G shiplap cladding  
 38x50 (34x45mm) prepared framework  
 Diagonal bracing for extra building strength  
 16x125 (12x119mm) T&G floor & roof  
 24kg felt, fittings, padbolt  
 Floor or no floor option to run area  
 Internal partition with door  
 Mesh door to run area  
 1 fixed window, 2 vents for air circulation  
 Instructions for self assembly  
 Height to eaves - 6'2" int (Approx.)  
 Height to ridge - 7'2" int (Approx.)

Optional Extras Available - See Page 34 For Full List

**Perfect for all kinds of animals, Dogs, Cats, Birds, Rabbits, Guinea pigs, Chickens Ducks and more. Please consider the required size of living and run area when ordering for your chosen pet. The run area can be with or without a timber floor.**

We can build to any size and design

## Model: Open Bar



8x6 Featheredge, Pressure Treated & Solvent Treated



Standard Specification Includes:

### FEATHEREDGE CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 25 x150 (15>5mm) featheredge cladding  
 38x50 (34x45mm) prepared framework  
 Diagonal bracing for extra building strength  
 16x125 (12x119mm) T&G floor and roof  
 24kg felt, fittings  
 12" Roof overhang as standard  
 Instructions for self-assembly  
 Low Height 6'3" int (Approx.)  
 High Height 7'1" int (Approx.)

Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth:

| 6' x 6' | 8' x 6' | 10' x 6' | 12' x 6' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 10' x 10' | 12' x 10' | 14' x 10' |

## Model: Garden Bar



10x6ft, Left Hand Stable Security Door Upgrade,  
 Pressure Treated & Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 16x125mm (12x119mm) T&G shiplap cladding  
 38x50mm (34x45mm) prepared framework  
 Diagonal bracing for extra building strength  
 16x125mm (12x119mm) T&G floor & roof  
 24kg felt, fittings, lock & key  
 Standard shed door, side hung hatch  
 Front hung hatch with supports  
 15" workbench to one side  
 Instructions for self assembly  
 Height to eaves - 6'2" int (Approx.)  
 Height to ridge - 7'2" int (Approx.)

Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth:

| 8 x 6' | 10' x 6' | 12' x 6' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 10' x 10' | 12' x 10' | 14' x 10' |

We can build to any size and design

## Model: Gazebo



8x8ft, Rustic Roof, Pressure Treated & Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 16x125 (12x119mm) T&G shiplap cladding  
 47x75 (45x70mm) prepared framework  
 Diagonal bracing for extra building strength  
 16x125 (12x119mm) T&G floor & roof  
 24kg felt, fittings  
 Instructions for self-assembly  
 Can have balustrade, half boarded or fully  
 boarded sections,  
 In any combination, at no additional cost.  
 Height to eaves - 6'9" int (Approx.)  
 Height to ridge - 7'10" int (Approx.)



**Gazebos and Logstores can be added to the side or back of most buildings.**

Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth:

| 8' x 6' | 10' x 6' | 12' x 6' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 10' x 10' | 12' x 10' | 14' x 10' |

We can build to any size and design

# POTTING SHED



Model: Potting Shed



18x10ft, Double Doors, Pressure Treated & Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction (Untreated)  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
2 opening windows, single door  
Glass Included  
24kg felt, fittings, lock & key  
Instructions for self-assembly  
Height high side - 7'2" int (Approx.)  
Height low side - 6'4" int (Approx.)



8x8 Onduline Roof  
Pressure Treated & Solvent Treated



16x10, Partition, Double Doors  
Pressure Treated & Solvent Treated



10x6, Partition, Extra Door  
Pressure Treated



10x8, Stable Security Door  
Pressure Treated & Solvent Treated



10x8, Stable Security Door  
Pressure Treated & Solvent Treated



8x8 Onduline Roof  
Pressure Treated & Solvent Treated

## Popular Sizes: Width X Depth:

| 6' x 6' | 8' x 6' | 10' x 6' | 12' x 6' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 10' x 10' | 12' x 10' | 14' x 10' |



Optional Extras Available - See Page 34 For Full List

We can build to any size and design

# POTTING SHED



Model: Snipe



10x8ft, Left Hand Door, Pressure Treated



10x6ft, Left Hand Door, Pressure Treated



8x6ft, Right Hand Standard Door  
Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
1 opening window, Toughened glass  
Stable door & potting bench  
24kg felt, fittings, lock & key  
Instructions for self-assembly  
Height high side 6'11" int (Approx.)  
Height low side 6'4" int (Approx.)

► Optional Extras Available - See Page 34 For Full



8x5ft, Left Hand Door, Pressure Treated

## Popular Sizes: Width X Depth:

| 8' x 6' | 10' x 6' | 12' x 6' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' | 10' x 10' | 12' x 10' | 14' x 10' |

We can build to any size and design

# SUMMER HOUSE / CHALET RANGE



Model: Raven



68x6 Raven, Pressure Treated & Solvent Treated, Rustic Roof



Standard Specification Includes:

## QUALITY LOGLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
22" Roof overhang as standard  
1 opening & 2 fixed windows  
Diamond leaded glass  
24kg felt, flower boxes  
Fittings, glass, single glazed door, lock & key  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 7'10" int (Approx.)

## Popular Sizes: Width X Depth

| 6' x 8' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' |



Optional Extras Available - See Page 34 For Full List



Model: Swift



8X8ft Tanalised Building, Solvent Rustic Roof



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
22" Roof overhang as standard  
4 opening side windows with vents &  
2 front fixed windows  
24kg felt, fittings, glass, lock & key  
Double doors with antique door furniture  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 7'10" int (Approx.)

## Popular Sizes: Width X Depth

| 6' x 8' | 8' x 8' | 10' x 8' | 12' x 8' | 14' x 8' |



Optional Extras Available - See Page 34 For Full List

We can build to any size and design

# SUMMER HOUSE / CHALET RANGE



Model: Nightingale / Eagle



8x10ft EAGLE, Pressure Treated & Solvent Treated  
\* Wings Are Optional



## Popular Sizes: Width X Depth

| 6' x 8' | 8' x 8' | 6' x 10' | 8' x 10' | 10' x 10' |



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
22" Roof overhang as standard  
Wavey Fascia Boards Included  
4 opening side windows with vents &  
2 front fixed windows  
24kg felt, fittings, glass, lock & key  
Double doors with antique door furniture  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 7'10" int (Approx.)



Optional Extras Available - See Page 34 For Full List



Standard Specification Includes:



Model: Kestrel



6x10ft, Bearers, Pressure Treated & Solvent Treated

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
22" Roof overhang as standard  
24kg felt, fittings, glass  
Including 4 opening windows  
Double doors with antique furniture  
Lock and key  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)



Optional Extras Available - See Page 34 For Full List

## Popular Sizes: Width X Depth

| 6' x 8' | 8' x 8' | 6' x 10' | 8' x 10' | 10' x 10' |

We can build to any size and design

# SUMMER HOUSE / CHALET RANGE



Model: Mallard



6x12ft, Pressure Treated & Solvent Treated, Rubber Roof, Toughened



**Popular Sizes: Width X Depth**

| 6' x 12' | 8' x 12' | 10' x 12' | 12' x 12' |

Standard Specification Includes:

**QUALITY T&G SHIPLAP CLADDING**

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
24" Roof overhang as standard  
Wavey fascia boards included  
24kg felt, fittings, glass, lock & key  
Including 2 opening windows  
& 1 bay window  
Double doors with antique furniture  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 8'2" int (Approx.)



Optional Extras Available - See Page 34 For Full List



Standard Specification Includes:

**QUALITY T&G SHIPLAP CLADDING**

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
22" Roof overhang as standard  
Wavey fascia boards included  
24kg felt, fittings, glass, lock & key  
2 fixed windows  
2 opening windows with vents  
Double doors with antique furniture  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 8'2" int (Approx.)



Optional Extras Available - See Page 34 For Full List

**Popular Sizes: Width X Depth**

| 6' x 10' | 8' x 10' | 10' x 10' | 12' x 10' | 6' x 12' | 8' x 12' | 6' x 12' | 8' x 12' | 6' x 14' | 8' x 14' | 10' x 14' | 12' x 14' |

We can build to any size and design

# SUMMER HOUSE / CHALET RANGE



Model: Housemartin



12x14ft, Rustic Roof  
Pressure Treated & Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
24kg felt, fittings, glass, lock & key  
2 fixed & 2 opening windows  
Double doors with antique furniture  
Depth includes 4ft verandah  
Instructions for self-assembly  
Height to eaves 6'4" int (Approx.)  
Height to ridge 8'2" int (Approx.)



Model: Falcon



10x8ft, Double Glazed Glass  
Pressure Treated & Solvent Treated



Standard Specification Includes:

## QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
47x75 (45x70mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
21" Roof overhang as standard  
24kg felt, fittings, lock & key.  
Double glazed toughened glass  
Glass to ground double doors & windows.  
2 vented windows, 2 fixed windows  
Rear privacy window as standard  
Instructions for self assembly  
Low Height 6'7" int (Approx.)



Optional Extras Available - See Page 34 For Full List

## Popular Sizes: Width X Depth

| 12' x 6' | 14' x 6' | 16' x 6' | 12' x 8' | 14' x 8' | 16' x 8' | 12' x 10' | 14' x 10' | 16' x 10' | 12' x 12' | 14' x 12' | 16' x 12' |

We can build to any size and design

# SUMMER HOUSE / CHALET RANGE



Model: Hummingbird



16x12ft, Rustic Roof, Solvent Treated



Standard Specification Includes:

## LOGLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
47x75 (45x70mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor & roof  
24" Roof overhang as standard  
24kg felt, fittings, glass, lock & key  
Double doors with antique furniture  
2 fixed & 2 opening windows  
Instructions for self-assembly  
Height to eaves 8'10" int (Approx.)  
Height to ridge 9'10" int (Approx.)



Optional Extras Available - See Page 34 For Full List

## Popular Sizes: Width X Depth

| 8' x 16' | 10' x 16' | 12' x 16' | 14 x 16' | 16' x 16' | 8' x 12' | 10' x 12' | 12' x 12' | 14' x 12' | 16' x 12' |

## Optional Verandah's



3ft Verandah With Front Handrail



Verandah's can be added to all building's of all sizes and made to any width and depth.



4ft Verandah With Support Post.  
Fully Open



Optional seating also available.

We can build to any size and design

# CHILDRENS PLAYHOUSES



## Model: Jack & Jill



8x8ft, Pressure Treated & Solvent Treated



6x8ft, Rustic Roof, Pressure Treated & Solvent Treated

### Popular Sizes: Width X Depth

| 7' x 5' | 7' x 6' | 8' x 6' | 7' x 7' | 8' x 8' | 10' x 8' |

## Model: Manor House



Upper Floor



10x8'6"  
Pressure Treated & Solvent Treated



10x12'6", 2 Additional Windows, Window Boxes,  
Rustic Roof, Pressure Treated & Solvent Treated



### Sizes: Width X Depth

| 10x8'6" | 10x10'6" | 10x12'6" | 10x14'6" |



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
16" Roof overhang as standard  
Wavey fascia boards included  
Upper floor with safety rail and ladder  
24kg felt & fittings, perspex, stable door  
4 fixed windows, flower boxes  
Instructions for self assembly  
Height to low eaves ridge 6' int (Approx.)  
Height to high eaves 6'4" int (Approx.)  
Height to ridge 7'5" int (Approx.)

Optional Extras Available - See Page 34 For Full



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
Wavey fascia boards included  
Upper floor with safety rail and ladder  
24kg felt, fittings, flower boxes  
Joinery door & 5 fixed windows, safety perspex  
Instructions for self assembly  
Height to eaves 6' int (Approx.)  
Height to ridge 7' int (Approx.)

\* Also available in log-lap cladding \*

Optional Extras Available - See Page 34 For Full List

**IMPORTANT: Playhouses with upper floors are not recommended for unsupervised play for children under 36 months of age.**

We can build to any size and design

# CHILDRENS PLAYHOUSES



Model: Alpine



8x10ft ( One Size Only ) Side Shed Not Included

**Size: Width X Depth:**

| 8' x 10' |



Optional Extras Available - See Page 34 For Full List

Model: Bart & Lisa



6x8ft + 2ft Verandah, Blue Fascia Pack  
Pressure Treated & Solvent Treated

**Popular Sizes: Width X Depth**

| 8' x 6' | 8' x 8' | 10' x 8' |



Optional Extras Available - See Page 34 For Full List

**IMPORTANT:** Playhouses with upper floors are not recommended for unsupervised play for children under 36 months of age.

We can build to any size and design

# CHILDRENS PLAYHOUSES



## Model: Bikers Rest



6x9ft, Pressure Treated & Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
Wavey fascia boards included  
24kg felt, fittings, safety perspex  
2 joinery doors & 3 fixed windows  
Partition included  
Instructions for self assembly  
Height to eaves 4'7" int (Approx.)  
Height to ridge 6'2" int (Approx.)

## Popular Sizes: Width X Depth

| 9' x 6' | 12' x 6' |



Optional Extras Available - See Page 34 For Full List

## Model: Den



5x5ft, Pressure Treated & Solvent Treated, Rubber Roof



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
24kg felt, fittings, safety perspex  
3 fixed windows  
Flower boxes, stable door  
Instructions for self assembly  
Height to eaves 5' int (Approx.)  
Height to ridge 6'1" int (Approx.)

## Popular Sizes: Width X Depth

| 5' x 5' | 6' x 6' | 7' x 7' |



Optional Extras Available - See Page 34 For Full List

**IMPORTANT: Playhouses with upper floors are not recommended for unsupervised play for children under 36 months of age.**

We can build to any size and design

# CHILDRENS PLAYHOUSES



## Model: Play House



8x8ft with Seating, Pressure Treated & Solvent Treated



\* Images Shown With Shiplap Cladding

### Popular Sizes: Width X Depth

| 7' x 7' | 8' x 8' |

## Model: Ranch House



8x8ft, Rustic Roof, Pressure Treated & Solvent Treated



### Size: Width X Depth

| 8' x 8' |



Optional Extras Available - See Page 34 For Full List



Standard Specification Includes:

### QUALITY LOGLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
25x125 (20x119mm) Loglap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
24kg felt, fittings, safety perspex  
4 fixed windows  
Flower boxes, joinery door  
Instructions for self assembly  
Height to eaves 4'11" int (Approx.)  
Height to apex 6'2" int (Approx.)  
\* Front Benches or Flower Boxes



Optional Extras Available - See Page 34 For Full List



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
24kg felt, fittings, safety perspex  
Joinery door & 3 fixed windows  
Fixed shutters  
Instructions for self assembly  
Height to eaves 4'10" int (Approx.)  
Height to apex 6'3" int (Approx.)



Optional Extras Available - See Page 34 For Full List

**IMPORTANT: Playhouses with upper floors are not recommended for unsupervised play for children under 36 months of age.**

We can build to any size and design

# CHILDRENS PLAYHOUSES



## Model: Shopkeepers Cabin



8x6ft, Solvent Treated ( Sign Not Included )



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
Wavey fascia boards included  
24kg felt, fittings, safety perspex  
Joinery door & 2 fixed windows  
Optional partition  
Instructions for self assembly  
Height to eaves 5'3" int (Approx.)  
Height to apex 6'6" int (Approx.)



Optional Extras Available - See Page 34 For Full

### Popular Sizes: Width X Depth

| 7' x 4' | 7' x 5' | 7' x 6' | 7' x 7' | 7' x 8' | 7' x 9' | 7' x 10' | 8' x 4' | 8' x 5' | 8' x 6' | 8' x 7' | 8' x 8' | 8' x 9' | 8' x 10' |

## Model: Wendy House



6x4ft, Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
38x50 (34x45mm) prepared framework  
16x125 (12x119mm) T&G floor & roof  
24kg felt, fittings, safety perspex  
Flower boxes, stable door  
3 fixed windows  
Instructions for self assembly  
Height to eaves 5' int (Approx.)  
Height to apex 6'1" int (Approx.)

### Popular Sizes: Width X Depth

| 5' x 3' | 5' x 4' | 6' x 4' | 7' x 5' | 8' x 5' | 8' x 6' |



Optional Extras Available - See Page 34 For Full List

**IMPORTANT: Playhouses with upper floors are not recommended for unsupervised play for children under 36 months of age.**

We can build to any size and design

## Featheredge Mini Shed



4x8ft, Apex Roof, Rustic Roof, Pressure Treated & Solvent Treated



Standard Specification Includes:

### FEATHEREDGE CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 25x150 (15>5mm) Featheredge cladding  
 38x50 (34X45mm) prepared framework  
 Diagonal bracing for extra building strength

16x125 (2x119mm) T&G floor & roof  
 24kg felt, fittings, padbolt

Double doors ( max 3ft less than width of building )  
 Instructions for self assembly

**APEX DESIGN:** Height to Eaves 4'11" - Height to Apex 5'11" int  
**PENT DESIGN:** Height High Side 5'2" - Height Low Side 4'11" int

\* Can be Apex or Pent roof \*



Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth

| 3' x 2' | 4' x 2' | 5' x 2' | 6' x 2' | 7' x 2' | 3' x 3' | 4' x 3' | 5' x 3' | 6' x 3' | 7' x 3' | 4' x 4' | 5' x 4' | 6' x 4' | 7' x 4' | 8' x 4' |

## Shiplap Mini Shed



6x3ft, Pent Roof, Solvent Treated



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )  
 Scandinavian redwood pine throughout  
 16x125 (12x119mm) T&G shiplap cladding  
 38x50 (34x45mm) prepared framework  
 Diagonal bracing for extra building strength  
 16x125 (12x119mm) T&G floor & roof  
 Double doors ( max 3ft less than width of building )  
 24kg felt, fittings & padbolt  
 Instructions for self assembly

**APEX DESIGN:** Height to Eaves 4'11" - Height to Apex 5'11" int

**PENT DESIGN:** Height High Side 5'2" - Height Low Side 4'11" int

\* Can be Apex or Pent roof \*



Optional Extras Available - See Page 34 For Full List

### Popular Sizes: Width X Depth

| 3' x 2' | 4' x 2' | 5' x 2' | 6' x 2' | 7' x 2' | 3' x 3' | 4' x 3' | 5' x 3' | 6' x 3' | 7' x 3' | 4' x 4' | 5' x 4' | 6' x 4' | 7' x 4' | 8' x 4' |

We can build to any size and design

# MINI SHEDS



## Model: Tall Store



\* With Optional Rustic Roof



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction (untreated)  
Scandinavian Redwood Pine Throughout  
16x125 (12x119mm) T&G Shiplap Cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings, lock & key  
Instructions for self-assembly

**APEX DESIGN:** Height to Eaves 6' - Height to Apex 6'8" int

**PENT DESIGN:** Height High Side 6'8" - Height Low Side 6'4"



\* With Optional Security Door  
& Rustic Roof

### Popular Sizes: Width X Depth

| 3'6" x 2' | 4'6" x 2' | 3'6" x 2'6" | 4'6" x 2'6" |

## Model: Log Store



\* Shows With Optional Rustic Roof



Standard Specification Includes:

### QUALITY T&G SHIPLAP CLADDING

100% timber construction (untreated)  
Scandinavian Redwood Pine Throughout  
16x125 (12x119mm) T&G Shiplap Cladding  
38x50 (34x45mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
24kg felt, fittings. Instructions for self-assembly  
Low Height: 3.'10" int.  
High Height : 4'2" int (Approx.)

**Can be Apex or Pent.**

**Can be built to any size to fit your space.**

### Popular Sizes: Width X Depth

| 3' x 2' | 4' x 2' | 5' x 2' | 6' x 2' | 7' x 2' | 3' x 3' | 4' x 3' | 5' x 3' |  
| 6' x 3' | 7' x 3' | 4' x 4' | 5' x 4' | 6' x 4' | 7' x 4' | 8' x 4' |

We can build to any size and design

# MINI SHEDS



MODEL: DUAL TALLSTORE / LOGSTORE



6x3ft, Pressure Treated & Solvent Treated, Bearers

Standard Specification Includes:

#### QUALITY T&G SHIPLAP CLADDING

100% timber construction ( Untreated )

Scandinavian redwood pine throughout

16x125 (12x119mm) T&G shiplap cladding

38x50 (34x45mm) prepared framework

Diagonal bracing for extra building strength

16x125 (12x119mm) T&G floor & roof

Single door, Partition, 24kg felt, fittings, Lock & Key  
Instructions for self assembly

**APEX DESIGN:** Height to Eaves 4'11" - Height to Apex 5'11" int

**PENT DESIGN:** Height High Side 5'2" - Height Low Side 4'11" int

\* Can be Apex or Pent Roof \*

MODEL: THAT'S HANDY



Standard Specification Includes:

#### QUALITY T&G SHIPLAP CLADDING

100% timber construction (untreated)

Scandinavian Redwood Pine Throughout

16x125 (12x119mm) T&G Shiplap Cladding

38x50 (34x45mm) prepared framework

16x125 (12x119mm) T&G floor and roof

24kg felt, fittings. Instructions for self-assembly  
Low Height 2'5" int - Hi Height 2'10" int (approx.)

\* Perfect for parcels & garden toys \*

#### Building Size

2'7" x 1'9" | 5'2" x 1'9" |

MODEL: GARDEN TIDY



4'6x2'6, Pressure Treated & Solvent Treated, Bearers

Standard Specification Includes:

#### QUALITY T&G SHIPLAP CLADDING

100% timber construction (untreated)

Scandinavian Redwood Pine Throughout

16x125 (12x119mm) T&G Shiplap Cladding

38x50 (34x45mm) prepared framework

Diagonal bracing for extra building strength

16x125 (12x119mm) T&G floor and roof

24kg felt, fittings. Instructions for self-assembly  
Padbolt. Door variations to customer requirements.

Low Height high: 3'3" int.

High Height : 3'6" int (Approx.)

#### Building Size

4'6" x 2'6"

We can build to any size and design

# ROOFING OPTIONS



## ONDULINE ROOFING

**Onduline Classic:** An extremely tough, lightweight, corrugated roofing system, made from recycled cellulose fibres and is suitable for a range of applications.

The lightweight roofing sheets are suitable for both renovation and new construction, and can be used on either wooden or metal structures.

The sheets are finished with a colour pigment and resin impregnation process which "stains" the colour into the sheet to provide excellent colour retention properties and enhanced U.V. resistance.

Onduline Classic roof solution is the perfect roof product for water tightness as well as providing thermal and acoustic comfort.



## RUSTIC ROOF

Our **Rustic Roof** option offers not only an attractive look but a complete protection from overhanging tree branches and falling debris, lowering maintenance required and extending the life of your building.

The Rustic Roof is constructed from Pressure Treated Featheredge boards and 38x50 framing.

Solvent based treatment is included with every rustic roof.

The **Rustic panels** are fitted over the top of your buildings felt roof.



## RUBBER ROOFING

**Upgrade your roof today with Shed Rubber 1.14mm EPDM Membrane.**

Increase your shed roofs longevity, durability and protection.

Our Shed Rubber EPDM Membranes are designed especially for your shed roofs. Because these membranes are only 1.14mm in thickness, our rubber EPDM membranes are incredibly lightweight and won't be a strain on your sheds' structure.

Rubber EPDM membranes have been trialled and tested to be **effective for 50 years** or more.

We can build to any size and design

# SECTIONAL BUILDINGS



We offer a large range of wooden sectional garden workshop sheds, workshop buildings, garden offices and timber cabins. Our sectional buildings are ideal for those looking to add the extra space that smaller garden sheds simply don't offer.



Size: 20' x 18'



## SECTIONAL SHEDS & WORKSHOPS

We manufacture sectional garden sheds in many shapes and sizes, all of which can be further customised to perfectly meet your needs.

You can choose from a wide range of optional extras such as bespoke doors, additional windows, alternative lining and insulation, extra partitions, extra height, thicker cladding, thicker floorboards, guttering, rubber roof and onduline roofing.

We build all of our sectional workshops to a high standard for long-lasting wear and tear which remain solid in adverse weather conditions.



Fully Customisable

We offer a large range of quality sectional sheds and garden workshops to suit all tastes and budgets.



Size: 8' x 16'



Size: 14' x 12'



Size: 33 x 17'



Size: 20 x 20'



Size: 18' x 8'



Size: 20' x 18'

We can build to any size and design

# SECTIONAL BUILDINGS




Size: 18' x 18'



Size: 25' x 10'




Size: 12' x 15'



Size: 40' x 17'



Size: 60' x 20'



Size: 45' x 15'



## STANDARD SPECIFICATIONS

100% timber construction ( Untreated )  
Scandinavian redwood pine throughout  
16x125 (12x119mm) T&G shiplap cladding  
47x75 (45x70mm) prepared framework  
Diagonal bracing for extra building strength  
16x125 (12x119mm) T&G floor and roof  
1 pair of standard double doors  
6'2" high X any width up to 8'0" wide  
(except 18' and 20' wide buildings which include  
2 sets of double doors )  
1 single personal door 6'2"x3'0" wide with lock  
1 opening and 2 fixed 2'x2' glazed windows  
Eaves height 6'7" internal  
Ridge height external ( varies with width of building )



## OPTIONAL EXTRAS

Additional doors  
Additional windows  
Lining and insulation  
Partitions ( up to eaves height )  
Extra height  
Thicker cladding & thicker floor boards  
Fixing down  
Guttering  
Upgrade framing  
Upgrade to onduline bituminous roofing sheet  
Upgrade to EPDM rubber roofing  
Plus even more extras ( [see page 34](#) )

## Popular Sectional Shed Sizes: Width X Depth

| 12' x 8' to 20' x 8' | 10' x 10' to 20' x 10' | 12' x 12' to 20' x 12' | 16' x 14' to 20' x 14' | 16' x 18' to 20' x 18' | 16' x 20' to 20' x 20' |

We can build to any size and design

# SHED & SUMMERHOUSE



## SINGLE GLAZED WINDOWS & DOORS TO SUIT

With 3mm horticultural glass or upgrade to 4mm toughened glass.

Brown plastic fittings and metal hinges as standard.


1678x508mm



PATT10  
SAW

1'8" w x 5'6" h


1780x1092mm



PATT10  
DOORS

3'7" w x 5'10" h

1646x476mm



PATT10  
FIXED

1'7" w x 5'5" h


1678x716mm



PATT15  
SAW

2'4" w x 5'6" h


1780x1510mm



PATT15  
DOORS

5' w x 5'10" h


1646x685mm



PATT15  
FIXED

2'3" w x 5'5" h


1804x1280mm



GAZD4

4'2" w x 6' h


1804x1280mm



GAZD2

4'2" w x 6' h


1300x716mm



GAZ1

2'4" w x 4'3" h

1300x716mm



GAZ2

2'4" w x 4'3" h


1300x716mm



GAZ4

2'4" w x 4'3" h


1780x1510mm



FG15  
DOORS

5' w x 5'10" h

1010x685mm



CG9

2'3" w x 3'4" h


1010x685mm



DR2

2'4" w x 3'5" h

1780x1510mm



2XG  
DOORS  
WIDE

5' w x 5'10" h

1010x685mm




CL3

2'3" w x 3'4" h

Double Security Garage Doors

2140x1980mm




GAR1

7' w x 6'6" h

Double Security  
Doors

1510x1780mm



PAIR  
FLB1

Security  
Door

755x1780mm



FLB1

5' w x 5'10" h 2'6" w x 5'10" h

\* ALL SIZES ARE APPROXIMATE \*

# DOUBLE GLAZED WINDOWS & DOORS




## WORKSHOPS / STORAGE & SECTIONAL BUILDINGS



Our range of double glazed windows and doors can be installed in sheds that are a minimum 47x75 framework such as the Woodcock, Woodpecker models and sectional buildings.

### DOUBLE GLAZED WINDOWS AND DOORS TO SUIT

1043x1158mm



1043x1158mm



3'5" w x 3'9" h

1462x1158mm




1462x1158mm



4'10" w x 3'9" h

1536x1158mm



1536x1158mm



5'w x 3'9" h

856x1965mm



6'5" w x 2'11" h

1618x1965mm



6'5" w x 5'4" h

760x392mm

SECURITY WINDOW

Security window  
available as 3  
pane or single.

2'6" w x 1'3" h


With 4mm toughened glass either side of a 6mm double glazed unit.

Chrome fittings as standard, locks to all openings and 3 lever door lock.



### DOUBLE GLAZED DOORS AND WINDOWS TO SUIT

550x1965mm



T10

1200x1965mm




T10 DOORS

550x1965mm




T10 LEA

760x1965mm



T15

1618x1965mm



T15 DOORS

760x1965mm



T15 LEA

856x1965mm



TS15 DOOR

1'9" w x 6'5" h

3'11" w x 6'5" h

1'9" w x 6'5" h

2'6" w x 6'5" h

5'3" w x 6'5" h

2'6" w x 6'5" h

2'9" w x 6'5" h

With 4mm toughened glass either side of a 6mm double glazed unit.

Chrome fittings as standard, locks to all openings and 3 lever door lock.

ALL SIZES ARE APPROXIMATE

# INSULATION & LINING OPTIONS



Topwood can insulate and line your building after 1<sup>st</sup> phase electrics are fitted to hide away the cables, this service must be requested at point of sale.



## BREATHER MEMBRANE - MOISTURE BARRIER

3-layer, High performance, yet lightweight, breather membrane designed for use in all insulated wall, floor and ceiling applications.

This membrane has an excellent Class W1 water resistance but still provides high breathability.

## EARTHWOOL INSULATION

100mm thickness with a thermal conductivity of 0.044 W/mK. Earthwool is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

(50mm used in shed framing buildings, all floors insulated with 25mm Quinn Therm as standard).

## CELOTEX INSULATION

50mm Quinn Therm has top-performing thermal conductive properties for use in floors, roofs and walls. The low thermal conductivity of Quinn Therm boards maximise the performance of their insulation properties and enables low U-values to be achieved.

All Quinn Therm PIR Insulation boards have zero Ozone Depletion Potential (ODP) and a A+ green guide rating, making them not just thermally efficient but will improve the overall sustainability of the building.

Quinn Therm PIR Insulation has a thermal conductivity of 0.022W/mK, making it one of the most effective rigid insulation boards available.

We can build to any size and design

# AVAILABLE OPTIONAL EXTRAS



Pent Sheds/ Apex Sheds / Workshops / Summer House-Chalet / Playhouses / Potting & Mini Sheds

The following shows the current available optional extras.  
Other optional extras, other sizes and variations may be available on request.



Available in Various Sizes

Installation

Bearers

Heavy Duty Cladding

Pressure Treated Upgrade

Solvent Treatment (light brown)

Rustic Roof

Onduline Roof

Rubber Roof

Overhang to Roof

25mm Loglap Cladding

4x2 Framing Upgrade

Hook & Band Hinges ( only on security doors )

Coach Bolt Hinges

Extra Height

Double Glazed Windows & Doors

No Floor

Partition

Guttering & Downpipe (not available with rustic roofs)

Toughened Glass

Shelves & Workbenches

Wider Door / Extra Door

Security Door / Double Doors

Joinery Summer house Doors

Security Windows

Extra Windows

Opening Windows

Leaded Windows

Joinery Summer house Windows

Window Boxes

Sealed Units (double glazed)

Lining Paper (moisture barrier)

Insulation & Plywood Lining

Insulation & Tongue & Groove

Matchboard Lining

PVC Membrane (secondary moisture barrier)

Thicker Floor Boards



## Treatment and Installation Service Available

\* All shed sizes shown in the images are approximate.

\* Prices and specifications are subject to alteration without prior notice.

\* Site preparation is the customer's responsibility and the base should be firm and level.

\* Ridge and eave heights are only approximate and are not guaranteed measurements.

## TOPWOOD GUARANTEE

**1 year against faulty parts and workmanship**

**10 years against rot providing the building is treated on a regular basis from the time of supply**



## QUALITY SHEDS BUILT TO LAST



### >>> BASE PREPARATION

The area should be firm and level by laying either paving slabs over the whole area, or a concrete base. We can supply treated timber bearers as an optional extra to stand your shed on but the area will still need to be firm, level, and clear of any foliage or grass. An extra charge may result if we are unable to erect your building due to the base not being firm or level.

**IF IN ANY DOUBT PLEASE ASK.**

### >>> SITE ACCESS

Please advise us when ordering your building of any access problems there are on your site, i.e entrance through house/garage, over fences, and any height restrictions ( i.e. archways, bars, and over gates ). An extra charge may result if we are unable to deliver your building due to not being advised of any access issues.

**IF IN ANY DOUBT PLEASE ASK.**

### >>> TIMBER BUILDING SIZES

All timber sizes quoted are nominal i.e before machining. All floor sizes are approximately 4" less in width and length than the shed size quoted. Please ask if an exact floor size is needed for base preparation.

You can order with confidence knowing that our skilled workforce produces a first-class range of timber sheds and buildings using carefully selected raw materials. Our purpose fleet of vehicles enables us to make fast and efficient delivery to your door.

### TOPWOOD GUARANTEE

1 Year against faulty parts and workmanship.

10 years against rot provided the building is treated on a regular basis from the time of supply.

**Approved Distributor For  
Topwood Garden Buildings Ltd**

